Copyright ©2018 - à¹€à¸„à¸£à¸·à¹ˆà¸-à¸‡à¸¡à¸·à¸-à¸§à¸´à¸—à¸¢à¸²à¸¨à¸²à¸ªà¸•à¸£à¹Œ à¸-à¸¸à¸›à¸•à¸£à¸“à¹Œà¹€à¸„à¸£à¸·à¹ˆà¸-à¸‡à¸§à¸±à¸”à¸ª

Copyright ©2018 - à¹€à¸„à¸£à¸·à¹ˆà¸-à¸‡à¸¡à¸·à¸-à¸§à¸´à¸—à¸¢à¸²à¸¨à¸²à¸ªà¸•à¸£à¹Œ à¸-à¸¸à¸›à¸à¸£à¸“à¹Œà¸à¸µà¸¬à¸²à¸ªà¸•à¸£à¹Œà¸ª

Copyright ©2018 - à¹€à¸„à¸£à¸·à¹ˆà¸-à¸‡à¸¡à¸·à¸-à¸§à¸´à¸—à¸¢à¸²à¸¨à¸²à¸ªà¸•à¸£à¹Œ à¸-à¸¸à¸›à¸à¸£à¸“à¹Œà¸ªà¸³à¸™à¸±à¸à¸‡à¸²à¸™à¸„à¸³à¸™à¸§à¸“à¸ª

à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸¡à¸·à¸-à¸§à¸±à¸” à¹€à¸„à¸£à¸·à¹^à¸-à

à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸¡à¸·à¸-à¸§à¸´à¸—à¸¢à¸²à¸¨à¸²à¸ªà¸•à¸£à¹Œà¸-à¸¸à¸›à¸•à¸£à¸“à¹Œà¸§à¸´à¸—à¸¢à¸²à¸¨à¸²à¸ªà¸•à¸£à¹Œà¸à¸²à¸£à¸µà¸§à¸´à¸•à¸ª à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸¡à¸·à¸-à¸§à¸±à¸” à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸¡à¸·à¸·

à¹€à¸„à¸£à¸µà¹^à¸-à¸‡à¸§à¸±à¸”à¸•à¸£à¸”à¸”à¹^à¸²à¸‡ pH Meter CyberScan PC300

à¸ªà¸-à¸šà¸–à¸²à¸¡à¸£à¸²à¸„à¸²

à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸§à¸±à¸”à¸„à¸µà¹^à¸²à¸žà¸µà¹€à¸-à¸Š **à¹€à¸„à¸£à¸µà¹^à¸-à¸‡à¸§à¸±à¸”à¸•à¸£à¸”à¸”à¹^à¸²à¸‡** à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸§à¸±à¸”à¸„à¸µà¹^à¸²à¸žà¸™à¹‰à¸³

à¹€à¸„à¸£à¸·à¹^à¸-à¸§à¸±à¸”à¸„à¸§à¸²à¸¡à¹€à¸›à¹‡à¸™à¸•à¸£à¸“ à¸”à¹^à¸²à¸‡ ***PH meter*** > CyberScan PC 300

Product Features

:: Waterproof and Dustproof Housing - IP67 rated, ideal for rugged harsh conditions. Plus it floats!
:: Multi-parameter - toggle between pH/temperature and Conductivity/temperature at touch of buttons
:: Multi-Point Push-button Calibration (up to 3/4 points for pH/Conductivity) - for easy, quick calibration
:: Auto-Buffer Recognition for pH calibration - no calibration mistakes
:: Auto-Ranging for Conductivity measurements for fast response and best resolution over measurement range
:: User-Customization for enhanced flexibility and viewing of Conductivity/TDS effective cell constants per range, electrode diagnosis - pH slope/offset/mV base value, previous calibration points, etc.
:: Stability Indicator prompts whenever reading stabilizes
:: Auto-Hold Function automatically freezes reading when stabilized for easy viewing and recording
:: Auto-Power Off saves battery power after non-use
:: Self-Diagnostic with message codes for easy troubleshooting

Copyright ©2018 - à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸¡à¸·à¸-à¸§à¸´à¸—à¸¢à¸²à¸¨à¸²à¸ªà¸•à¸£à¹Œà¸-à¸¸à¸›à¸•à¸£à¸“à¹Œà¸§à¸´à¸•à¸ª à¹€à¸„à¸£à¸·à¹^à¸-à¸‡à¸§à¸±à¸”à¸•à¸£à¸”à¸”à¹^à¸²à¸‡

:: Large Easy-to-Read Custom LCD with simultaneous display provides optimum viewing with user-friendly icons
:: Easy Interchangeability of electrodes caters for other specialty electrodes for specific applications
:: Rugged Carrying Case (Included) provides handy on-site meter calibration and measurement

Specifications

Product Specification	Description
pH Range	-2.00 to 16.00 pH
Resolution & Accuracy	0.01 pH & Â± 0.01 pH
Conductivity Range	0 to 19.99, 199.9, 1999 ÂµS/cm; 19.99, 199.9 mS/cm
TDS Range	0 to 9.99, 99.9, 999 ppm; 9.99, 99.9 ppt,Â Max. 199.9 ppt (depending on factor setting)
Resolution & Accuracy	0.1, 1 mV & Â±0.1, 1 mV
Temperature Range	0 to 100.0 Â°C; 32.0 to 212 Â°F (Meter)
Resolution & Accuracy	0.1 Â°C & Â± 0.3 Â°C; 0.1 Â°F & 0.5 Â°F
No. of pH Calibration Points	Up to 5 points
pH Buffer Option	USA: pH 1.68, 4.01, 7.00, 10.01, 12.45 NIST: pH 1.68, 4.01, 6.86, 9.18, 12.45
No. of Conductivity Calibration Points	5 points (max. 1 per range)
Cond. to TDS Conversion Factor	0.40 to 1.00 (selectable)
Temperature Compensation	Automatic / Manual (0 to 100 Â°C)
Special Functions	Stability Indicator; Auto Power-Off after 30 minutes;Â Hold; Self-diagnostics messages
Power	4 'AAA' x 1.4V batteries

Water Quality Meter *à¹€à¸„à¸£à¸·à¹ˆà¸-à¸‡à¸§à¸±à¸”à¸„à¹ˆà¸²à¸žà¸µ-à¹€à¸-à¸Š*
à¹€à¸„à¸£à¸µà¹ˆà¸-à¸‡à¸§à¸±à¸”à¸•à¸£à¸§à¸จà¸ªà¸ภาพน้ำ à¹€à¸„à¸£à¸·à¹ˆà¸-à¸‡à¸§à¸±à¸”à¸„à¸¸à¸“à¸ภาพน้ำ
à¹€à¸„à¸£à¸·à¹ˆà¸-à¸§à¸±à¸”à¸„à¸§à¸²à¸¡à¹€à¸›à¹‡à¸™à¸•à¸£à¸´ à¸"à¹ˆà¸²à¸‡ ***PH meter*** > CyberScan PC300

à¸£à¸²à¸¢à¸¥à¸°à¹€à¸-à¸µà¸¢à¸"à¸œà¸¹à¹‰à¸.à¸²à¸¢